



i-6000 SERIES DRIVE UNIT

INTERNALLY SEALED FOR PROLONGED DRIVE UNIT LIFE

INTRODUCING THE i-6000 SERIES, INTERNALLY SEALED DRIVE UNIT.

The "New Standard" for Drive Units.

The next innovation from Hallco Industries, our new i-Series drive units feature anodized aluminum manifolds and internally sealed cylinder barrels, optimizing seal life in corrosive environments. Additional wear rings have been added to the head manifold/shaft bore providing replaceable wear surfaces and increasing drive unit life.

By moving the seal inside the cylinder barrel, the seal is positioned further away and protected from corrosive debris such as road salt, which ultimately prolongs drive unit life.

Features	Specifications
Load Rating	45 Ton
# Cylinders	6
Nominal Stroke	10"
Piston Diameter	3.5"
Shaft Coating	Double Chrome
Effective Piston Area	17.48 in ²
Rated Pressure	3000 PSI
Rated Flow	30 GPM
Theoretical Convey Speed (max flow)	5.3 ft/min
Mount Style	Under Mount
Convey Direction Options	One-Way & Two-Way
Hydraulic Module (only) Weight	260 lbs
Deck Compatibility	Standard Double Ridge Triple Ridge TOPSEAL [™] TUFDECK [™] Narrow Leak Resistant Narrow Leak Resistant HD